

Cable tie for high strength fixing

Made of Nylon 66 and 304 barb; this cable tie is a better choice for high strength applications.

Advantages at a glance



Stainless steel barb provides consistent performance and reliability and infinite adjustability through entire bundle range



High strength and low thread force



Stippled strap body prevents lateral movement on the bundle



Curved tip is easy to pick up from flat surface and allows faster initial threading to speed installation

Information

Our cable ties comply with the following directives:

- ABS (Product Approval)
- CE (Certificate of conformity)
- UL62275 (Cable management systems)
- Lloyd's Register
- DNV
- DNV GL
- RoHS

Characteristics

Material-Locking Barb: Stainless Steel 304
Working Temp: -40 °C to +85 °C
Color: Black and White
Flammability: UL94V-2
Other Properties: Halogen Free,
UV-resistant

(black cable ties)

Applications

- Electrical installations
- Industrial cabling
- Automotive cabling
- Marine cabling
- Panel building
- Special applications

Materials

Band: Nylon 66

Locking barb: SS 304 (W4)

Technical data & Ordering information

NORMAFIX® CABLE TIE WITH METAL BARB			
Width in mm	Designation	Length in mm	Black Product No.
2.4	CABLE TIE WITH METAL BARB 2.4 X 102	102	0892 7118 001
	CABLE TIE WITH METAL BARB 2.4 X 201	201	0892 7118 003
3.6	CABLE TIE WITH METAL BARB 3.6 X 155	155	0892 7118 006
	CABLE TIE WITH METAL BARB 3.6 X 200	200	0892 7118 009
	CABLE TIE WITH METAL BARB 3.6 X 284	284	0892 7118 007
4.8	CABLE TIE WITH METAL BARB 4.8 X 186	186	0892 7118 011
	CABLE TIE WITH METAL BARB 4.8 X 250	250	0892 7118 010
	CABLE TIE WITH METAL BARB 4.8 X 295	295	0892 7118 012
	CABLE TIE WITH METAL BARB 4.8 X 361	361	0892 7118 013
7.0	CABLE TIE WITH METAL BARB 7.0 X 221	221	0892 7118 016
	CABLE TIE WITH METAL BARB 7.0 X 378	378	0892 7118 018
	CABLE TIE WITH METAL BARB 7.0 X 699	699	0892 7118 021



Refer to pages 192 and 197