



- 1 Easy handling
- 2 Strong worm-drive hose clamp

The changeover connector with 2 lip seals

The NORMA**CONNECT**® CONFIX is a flexible connection which adapts to different pipe dimensions and materials.

Materials

W1	W2	W3	W4	W5
	x			

Material, Connector: EPDM

Material, Worm-drive hose clamp band: AISI 430

Main advantage



The connection of feed or suction lines to a pipe – either made of steel or plastics – is easily and safely achieved with the CONFIX connector.

Technical data & Ordering information

NORMACONNECT® DCS CONFIX, EPDM with TORRO W2, Changeover Connector											
Designation	DN	D1 (mm)	D3 (mm)	D4 (mm)	D5 (mm)	D7 (mm)	L1 (mm)	L3 (mm)	L8 (mm)	Insertion depth (mm)	W2 Product No.
CONFIX DN 50	50	72	56	30	67.5	57	63	19	19	42	0245 9003 050
CONFIX DN 70	70	92	75	41	86.5	77	77	19	24	55	0245 9003 070
CONFIX DN 80 56-75	80	92	75	41	91	81	77	19	24	55	0245 9003 075
CONFIX DN 80 75-90	80	108	90	58	93	81	88	19	23	60	0245 9003 080
CONFIX DN 100	100	128	110	78	118	108	95	21	23	65	0245 9003 100
CONFIX DN 125	125	145	126	90	145	132	103	26	27	75	0245 9003 125

